



 Class 1, Division 2,
Groups A, B, C, and D
Hazardous Locations.



Johnson Controls Metasys Slave Interface Module

3100-N2

The inRAx Johnson Controls N2 Communication Module allows Rockwell Automation PLC I/O compatible processors to interface easily with other Johnson Controls N2 master devices.

Features and Benefits

The inRAx module acts as an input/output module between the Johnson Controls N2 network and the Rockwell Automation backplane. The module acts as a slave receiving commands from a master device. The data transfer from the processor is asynchronous from the actions on the Johnson Controls Metasys network. An internal database in the module exchanges data between the processor and the Johnson Controls Metasys Master (NCM, N-30, NAE, NIE).

Functional Specifications

Some of the general specifications include:

- Support for the storage and transfer of internal database registers to/from the processor's N files.
- Two ports to emulate a Johnson Controls N2 slave
- Supports the following N2 objects:
 - Binary Input: Up to 960 points
 - Analog Output: Up to 300 points
 - Binary Output: Up to 960 points
 - Analog Output: Up to 300 points
- Supported Commands/Sub-commands
 - 0/4: Poll Message No Acknowledge
 - 0/5: Poll Message with Acknowledge
 - 0/9: Status Update
 - 1/1: Read Analog Input Attributes
 - 1/2: Read Binary Input Attributes
 - 1/3: Read Analog Output Attributes
 - 1/4: Read Binary Output Attributes
 - 2/1: Write Analog Input Attributes
 - 2/2: Write Binary Input Attributes
 - 2/3: Write Analog Output Attributes
 - 2/4: Write Binary Output Attributes
 - 7/2/3: Override Analog Output
 - 7/2/4: Override Binary Output
 - F: Identify Device Type

Johnson Controls Metasys Slave Interface Module

3100-N2

Ideal for Energy Management Applications

Applications benefiting from the N2 module are prevalent in commercial building and energy management projects. Single or multiple processor applications will benefit through reduced installation costs and increased functionality.

How to Contact Us: Sales and Support

All ProSoft Technology products are backed with unlimited technical support. Contact our worldwide Technical Support team directly by phone or email:

Asia Pacific

+603.7724.2080, asiapc@prosoft-technology.com
Languages spoken include: Chinese, Japanese, English

Europe – Middle East – Africa

+33 (0) 5.34.36.87.20, support.EMEA@prosoft-technology.com
Languages spoken include: French, English

North America

+1.661.716.5100, support@prosoft-technology.com
Languages spoken include: English, Spanish

Latin America (Sales only)

+1.281.298.9109, latinam@prosoft-technology.com
Languages spoken include: Spanish, English

Brasil

+55-11.5084.5178, eduardo@prosoft-technology.com
Languages spoken include: Portuguese, English

- The following commands are recognized, and acknowledged, but are not communicated in any way to the processor, and do not return any data:
 - 0/0: Time Update
 - 0/8: Warm Start
 - All other commands return a Bad Command Error Code
- Configurable through the configuration file for the following:
 - Slave Address (assignable individually for Port 1 and 2)
 - Analog Input Object Count
 - Binary Input Object Count
 - Analog Output Object Count
 - Binary Output Object Count
- Warning and Alarming functions performed on Analog Input and Binary Input data types
- Change of State Response buffering
- Communication status error codes and statistics returned per port

Memory mapping is pre-assigned to optimize data access and to ease implementation

A port configured as a Johnson Controls N2 slave permits a remote master to interact with data contained in the module. This data is derived from the processor.

Hardware Specifications

Specification	Description
Backplane current load	3100 module for PLC 0.65 A
Operating temperature	0 to 60°C (32 to 140°F)
Storage temperature	-40 to 85°C (-40 to 185°F)
Relative humidity	5 to 95% (non-condensing)
LED Indicators	Module status Backplane transfer status Serial port TX/RX activity LED Serial port error LED status
Application serial ports	DB-25F3100 module RS-232/422/485 jumper selectable RS-422/485 screw termination included (two per module) RS-232 hardware handshaking (RTS/CTS, DTR) 500V optical isolation from backplane

Additional Products

ProSoft Technology offers a full complement of hardware and software solutions for a wide variety of industrial communication platforms.

Visit our web site at <http://www.prosoft-technology.com> for a complete list of products.

Ordering Information

To order this product, please use the following:

3100-N2 Johnson Controls Metasys Slave Interface Module

To place an order, please contact your local ProSoft Technology distributor. For a list of ProSoft distributors near you, go to <http://www.prosoft-technology.com>

Distributors:

Place your order by email or fax to:

North American / Latin American / Asia Pacific

orders@prosoft-technology.com,
fax to +1 661.716.5101

Europe

europe@prosoft-technology.com,
fax to +33 (0) 5.61.78.40.52

Copyright © ProSoft Technology, Inc. 2000 - 2007. All Rights Reserved.
January 18, 2007