



Class 1, Division 2,  
Groups A, B, C, and D  
Hazardous Locations.



## Siemens SEABus Plus Master Communication Module 3100-SEA

The 3100-SEA (PLC) module is a single slot solution for the Rockwell Automation 1771 platforms. The module's capabilities are enabled and controlled with ladder logic and data table initialization.

### How to Contact Us: Sales and Support

All ProSoft Technology products are backed with unlimited technical support. Contact our worldwide Technical Support team directly by phone or email:

#### Asia Pacific

+603.7724.2080, asiapc@prosoft-technology.com  
Languages spoken include: Chinese, Japanese, English

#### Europe – Middle East – Africa

+33 (0) 5.34.36.87.20, support.EMEA@prosoft-technology.com  
Languages spoken include: French, English

#### North America

+1.661.716.5100, support@prosoft-technology.com  
Languages spoken include: English, Spanish

#### Latin America (Sales only)

+1.281.298.9109, latinam@prosoft-technology.com  
Languages spoken include: Spanish, English

#### Brasil

+55-11.5084.5178, eduardo@prosoft-technology.com  
Languages spoken include: Portuguese, English

# Siemens SEABus Plus Master Communication Module

## 3100-SEA

### Features and Benefits

The Siemens SEABus Plus Master Module allows the user to easily configure one or both ports to collect data from Siemens 4300, 4700 and Static Trip III devices. By providing configurable access to both ports, this product is able to communicate directly with multiple Siemens Power Meter devices.

ProSoft's ladder-programming package allows for simple module setup and operating control.

### Hands-Off Operation

After the SEA module has been setup for operation, the module provides transparent control and monitoring capabilities. The SEA module, integrated directly into the PLC/SLC rack, forms a tightly integrated and practical solution. After configuration, the module will perform all protocol related functions on a stand-alone basis.

### Functional Specifications

- Siemens SEABUS Plus Master protocol
- Full Multi-drop support with up to 32 slave devices per port
- Supports RS-485 interface directly to Multi-drop link of Siemens meters
- Slave polling controlled by user configuration of slave poll list
- Data objects for each of the device types are pre-defined, making implementation very easy
- Configuration via simple ladder logic
- Simple configuration of slave types:

Type	Description
1	4700 Meter Long data read
2	4700 Meter Short data read
3	4300 Meter
4	Static Trip III Short data read
5	Static Trip III Long data read

- Communication parameters:

Parameter	Value
Parity:	None, odd, even
Stop Bit:	1 or 2
Baud rate:	300 to 38.4K
RTS Delays:	1 ms resolution on and off

## Hardware Specifications

Specification	Description
Backplane current load	3100 module for PLC 0.65 A
Operating temperature	0 to 60°C (32 to 140°F)
Storage temperature	-40 to 85°C (-40 to 185°F)
Relative humidity	5 to 95% (non-condensing)
LED Indicators	Module status Backplane transfer status Serial port TX/RX activity LED Serial port error LED status
Application serial ports	DB-25F3100 module RS-232/422/485 jumper selectable RS-422/485 screw termination included (two per module) RS-232 hardware handshaking (RTS/CTS, DTR) 500V optical isolation from backplane

## Additional Products

ProSoft Technology offers a full complement of hardware and software solutions for a wide variety of industrial communication platforms.

Visit our web site at <http://www.prosoft-technology.com> for a complete list of products.

## Ordering Information

To order this product, please use the following:

**3100-SEA** Siemens SEABus Plus Master Communication Module

To place an order, please contact your local ProSoft Technology distributor. For a list of ProSoft distributors near you, go to <http://www.prosoft-technology.com>

### Distributors:

Place your order by email or fax to:

### North American / Latin American / Asia Pacific

[orders@prosoft-technology.com](mailto:orders@prosoft-technology.com),  
fax to +1 661.716.5101

### Europe

[europe@prosoft-technology.com](mailto:europe@prosoft-technology.com),  
fax to +33 (0) 5.61.78.40.52

Copyright © ProSoft Technology, Inc. 2000 - 2007. All Rights Reserved.

January 18, 2007