



# PROFIBUS DP Slave to HART Multi-drop Gateway

## 5507-PDPS-HART

The ProLinX PROFIBUS DP Slave to HART Multi-drop Gateway creates a powerful connection between devices on a PROFIBUS DP network and HART field devices. This stand-alone DIN-rail mounted protocol gateway provides one PROFIBUS DP Slave configurable DB9F port and 4 configurable HART Multi-drop channels.

The PROFIBUS DP Slave protocol driver supports the PROFIBUS V0 Slave implementation, providing powerful data transfer capability between the ProLinX module and Siemens PLCs or other hosts. User configurable data mapping and DP port operation make the interface an easy to use and powerful data transfer tool.

The HART protocol driver works as a Master on four (HART) or eight channels (HART2 – not available on certain configurations) per interface card, depending on implementation. Each channel is individually configurable.

## PROFIBUS DP Slave

The PROFIBUS DP Slave driver gives access to the ProLinX unit's internal database via 244 bytes of Input data and 244 bytes of Output data (maximum 400 bytes total). These Input and Output data blocks are mapped by the user within the ProLinX module's data memory allowing the user maximum flexibility and data transfer with other protocols.

### General Parameters

GSD File	PRLX05A5.GSD Downloadable from ProSoft Technology web site
----------	---

### PROFIBUS Specifications

Communication parameters	Baud Rate: 9.6 kbit/s – 12 Mbit/s
Supported I/O length	244 bytes Input data 244 bytes Output data 400 bytes total
Supported PROFIBUS DP features	PROFIBUS V0 Slave using Siemens SPC3 chipset Freeze Mode Sync Mode Auto Baud Setting
Configurable Parameters	PROFIBUS Node Address: 1 to 125 Data byte swapping Action on loss of PROFIBUS connection Comm Fail Timeout Multiplier Status Data location in Internal Database

## HART

The HART Master Protocol exists in 4 channel implementations with HART2 allowing 8 channels. This driver can be configured on an individual channel basis to operate as a HART Master Station and supports all the available HART commands including Universal, Common Practice and Device Specific Commands. Each HART

## PROFIBUS DP Slave to HART Multi-drop Gateway

### 5507-PDPS-HART

*The PDPS-HART modules are the ideal solution for the many applications where PROFIBUS DP connectivity can be used to integrate HART Multi-drop devices into a system. The PROFIBUS DP Slave gateway is a powerful module designed with Slave support, enabling easy connection to PROFIBUS master devices. In combination with the HART support, the module provides a very powerful interface to the more than two million HART devices which are in use in the industrial marketplace today. Applications for the module are found in most industries, especially Manufacturing, Oil and Gas, Electrical Power and Food Processing.*

## How to Contact Us: Sales and Support

All ProSoft Technology® products are backed with unlimited technical support. Contact our worldwide Technical Support team directly by phone or email:

### Asia Pacific

+603.7724.2080, asiapc@prosoft-technology.com  
Languages spoken include: Chinese, Japanese, English

### Europe – Middle East – Africa

+33 (0) 5.34.36.87.20, support.EMEA@prosoft-technology.com  
Languages spoken include: French, English

### North America

+1.661.716.5100, support@prosoft-technology.com  
Languages spoken include: English, Spanish

### Latin America (Sales only)

+1.281.298.9109, latinam@prosoft-technology.com  
Languages spoken include: Spanish, English

### Brasil

+55-11.5084.5178, eduardo@prosoft-technology.com  
Languages spoken include: Portuguese, English

channel is independently configured to interface with the internal database in the module.

The auto-poll mode allows the module to automatically collect data from each HART instrument on the channel and store the data in the module's database without the use of user commands. The module automatically generates HART commands 0, 3, 13, 14 and 15.

#### General Parameters

Communication parameters	Number of HART Preambles: 2 to 50 Enable Handheld: Y or N Primary Master: Y or N
Configurable Parameters per Channel	Auto-Poll Enable, Short / Long Address Retries, Retries After Error Poll Time After Error, Number of Commands, Slave List Error Pointer

#### HART Driver

Command List	Up to 100 fully configurable commands per channel
Polling of command list	User configurable polling of commands, including disabled, continuous, on change of data (write only) and dynamically user or automatic enabled.

HART® is a registered trademark of the HART Communication Foundation

### General Specifications

The ProLinx Communication Modules provide connectivity for two or more dissimilar network types. The modules, encased in sturdy extruded aluminum, are stand-alone DIN-rail mounted protocol gateways, providing communication between many of the most widely used protocols in industrial automation today.

### Hardware Specifications

Specification	Description
Power Supply	24 VDC nominal 18 to 36 VDC allowed Positive, Negative, GND Terminals 2.5 mm screwdriver blade
Current Load	500 mA max@ 24 VDC
Operating Temperature	0 to 50°C (32 to 122°F)
Storage Temperature	-40 to 85°C (-40 to 185°F)
Relative Humidity	5 to 95% (non-condensing)
Dimensions	Standard: 5.20H x 2.07W x 4.52D in. (13.2cmH x 5.25cmW x 11.48cmD) Extended: 5.20H x 2.73W x 4.52D in. (13.2cmH x 6.934cmW x 11.48cmD)
LED Indicators	Power and Module Status Application Status Serial Port Activity LED Serial Activity and Error LED Status
Configuration Serial Port	DB-9M RS-232 only No hardware handshaking

Specification	Description
Ethernet Port (Ethernet modules only)	RJ45 Connector Link and Activity LED indicators
Application Serial Ports	RS-232/422/485 RS-232 handshaking configurable RS-422/485 screw termination included
Serial Port Isolation	2500V RMS port signal isolation per UL 1577 3000V DC min. port to ground and port to logic power isolation
Shipped with Each Unit	Mini-DIN to DB-9M serial cables 4 ft RS-232 configuration cable 2.5mm screwdriver CD (docs and Configuration utility) RS-422/485 DB-9 to Screw Terminal Adaptor (1 or 4, depending on ports)

### ProSoft Configuration Builder

ProSoft Configuration Builder (PCB) provides a quick and easy way to manage module configuration files customized to meet your application needs. PCB is not only a powerful solution for new configuration files, but also allows you to import information from previously installed (known working) configurations to new projects.

### Additional Products

ProSoft Technology offers a full complement of hardware and software solutions for a wide variety of industrial communication platforms.

Visit our web site at <http://www.prosoft-technology.com> for a complete list of products.

### Ordering Information

To order this product, please use the following:

**5507-PDPS-HART** PROFIBUS DP Slave to HART Multi-drop Gateway

To place an order, please contact your local ProSoft Technology distributor. For a list of ProSoft distributors near you, go to <http://www.prosoft-technology.com>

#### Distributors:

Place your order by email or fax to:

**North American / Latin American / Asia Pacific**  
orders@prosoft-technology.com,  
fax to +1 661.716.5101

#### Europe

europe@prosoft-technology.com,  
fax to +33 (0) 5.61.78.40.52

Copyright © ProSoft Technology, Inc. 2000 - 2007. All Rights Reserved.  
May 03, 2007