



LP-25066 Lightning Protector

RadioLinX LP-25066 Lightning Protector is designed to provide protection for wireless systems with low RF power.

The LP-25066 lightning protector is designed for use externally to an enclosure with any bulkhead fitting. The connectors are a standard N jack plug to a standard N jack BH connector. The bulkhead fitting can be connected to any standard N type connector extension cable.

Features and Benefits

- Multi-strike capability
- Fully weatherized housing
- Low throughput energy
- DC blocked

Technical Specifications

Frequency Range	2000 - 6000 MHz
Insertion Loss	0.1 dB
RF Power	10 Watts
Temperature Operating/Storage	-40° C to +85° C (-40° F to 185° F)
Relative Humidity	0 to 100% condensing
Surge Throughput Energy	≤ 0.5000 μJ
VSWR	1.2:1

Additional Products

ProSoft Technology® offers a full complement of hardware and software solutions for a wide variety of industrial communication platforms.

Visit our web site at <http://www.prosoft-technology.com> for a complete list of products.

Ordering Information

To order this product, please use the following:

LP-25066 Lightning Protector

To place an order, please contact your local ProSoft Technology distributor. For a list of ProSoft distributors near you, go to <http://www.prosoft-technology.com>

Distributors:

Place your order by email or fax to:

North American / Latin American / Asia Pacific

orders@prosoft-technology.com,
fax to +1 661.716.5101

Europe

europe@prosoft-technology.com,
fax to +33 (0) 5.61.78.40.52

Copyright © ProSoft Technology, Inc. 2000 - 2008. All Rights Reserved.

2/8/2008

How to Contact Us: Sales and Support

All ProSoft Technology® products are backed with unlimited technical support. Contact our worldwide Technical Support team directly by phone or email:

Asia Pacific

+603.7724.2080, asiapc@prosoft-technology.com
Languages spoken include: Chinese, Japanese, English

Europe - Middle East - Africa

+33 (0) 5.34.36.87.20, support.EMEA@prosoft-technology.com
Languages spoken include: French, English

North America

+1.661.716.5100, support@prosoft-technology.com
Languages spoken include: English, Spanish

Latin America (Sales only)

+1.281.298.9109, latinam@prosoft-technology.com
Languages spoken include: Spanish, English

Brasil

+55-11.5084.5178, eduardo@prosoft-technology.com
Languages spoken include: Portuguese, English