

## DATASHEET

### PROFIBUS<sup>®</sup> Multi-Slave or PROFIBUS<sup>®</sup> Network Analyzer Gateway, non-CE

AN-X-PB

The PROFIBUS<sup>®</sup> Multi-Slave or PROFIBUS Network Analyzer Gateway has two distinct operational modes. The first mode, PROFIBUS Multi-Slave, enables the transfer of large amounts of data from a PROFIBUS DP Master controller to EtherNet/IP<sup>™</sup> and/or Modbus TCP-enabled PLCs. The Multi-Slave functionality allows up to 15,250 words of Input and Output data to be transferred without requiring multiplexing PLC code to be written in a traditional single slave solution. The second mode, PROFIBUS Network Capture, facilitates the capture, logging, and filtering of packets on a PROFIBUS network without interrupting the running production network. This enables a root cause analysis to be performed on the captured PROFIBUS packets which aids in the identification of complex issue(s).



#### PROFIBUS<sup>®</sup> Multi-Slave Features:

- ◆ Configures through a web browser (No special configuration software required)
- ◆ Configuration option of 1 to 125 PROFIBUS slaves
- ◆ Supports PROFIBUS Baud Rates of 9600 bps to 12 Mbps
- ◆ PROFIBUS Network monitoring tool shows network traffic to and from a user specified node address
- ◆ Ability to view configuration and diagnostics through a web browser enabling remote monitoring or troubleshooting
- ◆ Supports sending up to 250 words of input data, and 248 words of output data on an I/O connection to an Allen-Bradley<sup>®</sup> PLC
- ◆ Supports Class 3 message instructions to move data to Allen-Bradley PLCs
- ◆ Supports up to 16 Modbus TCP client connections
- ◆ Supports Modbus Function Codes 2, 3, 4, 5, 6, 15, 16



A product of Quest Technical Solutions

Sold and Supported by  
ProSoft Technology Inc.  
[www.prosoft-technology.com](http://www.prosoft-technology.com)



## PROFIBUS® Capture Features:

- ◆ Passively monitors all PROFIBUS packets sent across the network
- ◆ Capture file can be configured to use a circular buffer, to capture data for a specific amount of time, or to stop capturing after a specified number of errors have occurred.
- ◆ Filtering options include: Source Address, Destination Address, Frame Control Values, Detailed Status, Frame Data, and Frame CheckSum which enables only the data specified to be logged and displayed
- ◆ A filtering equation can be written to further limit the captured and displayed data
- ◆ Customizable time format
- ◆ Captured data can be saved for future use
- ◆ Passively monitors all PROFIBUS packets sent across the network

## Hardware Specifications

Specification	Description
Ports	1 RJ45 10/100 Mbps Ethernet port for EtherNet/IP™ connection 1 DB9 serial connector for the PROFIBUS network connection 1 Phoenix 3-pin power connector
Typical Power Consumption	300 mA @ 12 Vdc or 150 mA @ 24 Vdc
Maximum Power Dissipation	3.6W
Operating Temp	32° F to 122° F (0° C to 50° C)
Storage Temperature	-40° F to 185° F (-40° C to 85° C)
Dimensions	107 x 126 x 34 mm 4.18 x 4.97 x 1.33 in Not including connectors
Humidity	5% to 95% RH, with no condensation

Desktop use or DIN Rail Mountable

## Ordering Information

### PROFIBUS® Multi-Slave or PROFIBUS® Network Analyzer Gateway

#### AN-X-PB

### How to Contact Us: Sales and Support

Sales and Technical Support for this product are provided by ProSoft Technology. Contact our worldwide Sales or Technical Support teams directly by phone or email:

#### Asia Pacific

+603.7724.2080, asiapc@prosoft-technology.com

#### Europe – Middle East – Africa

+33 (0) 5.34.36.87.20, europe@prosoft-technology.com

#### North America

+1.661.716.5100, support@prosoft-technology.com

#### Latin America (Sales only)

+1.281.298.9109, latinam@prosoft-technology.com

Copyright © ProSoft Technology, Inc. 2017.  
All Rights Reserved. June 7, 2017