

EtherNet/IP™ to Remote I/O or DH+ Gateway AN-X2-AB-DHRIO

The AN-X2-AB-DHRIO Gateway is designed to help customers initiate a phased migration approach to replacing or upgrading legacy Remote I/O PLCs, HMI's, Drives or Flex I/O Adapters. These solutions can be achieved by selecting the corresponding operation mode during initial configuration. The AN-X2-AB-DHRIO has a built-in web server that can display diagnostics data, configuration, upload configuration files, and set the operation mode.



Note: Now supports DH+ migrations on SLC networks. Some PLC code change may be required see [TN143269-001 DH+ to EIP PV Migration for SLC networks.pdf](#) for more information.

DRIVE



This mode supports upgrading legacy Allen Bradley drives on Remote I/O to new EtherNet/IP enabled drives.

- No changes to PLC code required
- Supports up to 4 EtherNet/IP drives
- Configurable with 1/4, 1/2 and full rack addressing
- Supports all PowerFlex drives on EtherNet/IP

HMI



This mode allows legacy PanelViews on Remote I/O or DH+ to be upgraded to a PanelView Plus, PanelView Plus 6 or PanelView Plus 7 on EtherNet/IP.

- No changes to PLC code required
- Supports up to 8 PanelViews on the same network
- Support for DH+ to EtherNet/IP PanelViews upgrades on PLC5 or SLC networks


Remote I/O Scanner



This mode allows users to replace their existing Remote I/O PLC with a ControlLogix or CompactLogix PAC without having to replace existing racks of I/O.

- Build new controller program without interrupting existing controls, minimizing downtime
- Supports up to 32 racks of Remote I/O
- Supports all Remote I/O baud rates (57.6, 115.2, and 230.4 K baud), and Remote I/O addressing 0 to 76 octal
- Works with both ControlLogix or CompactLogix
- Auto-Configuration utility discovers baud rate and maps discrete I/O reducing configuration errors

DH+



This mode acts as a bridge between an EtherNet/IP and a Data Highway Plus network.

- Programming terminals, and/or processors on an EtherNet/IP network can access legacy processors on a DH+ network
- Download to a PLC5 or SLC through RSLinx
- Configures through web browser
- Supports all DH+ baud rates (57.6, 115.2, and 230.4 K baud)
- Support for DH+ to EtherNet/IP PanelViews upgrades on PLC5 or SLC networks

Flex I/O Scanner



This mode allows PLC's on Remote I/O to connect to and control 1794-AENT EtherNet/IP Flex adapters.

- Designed to replace obsolete 1794-ASB adapters
- Supports up to 16 EtherNet/IP connections
- Each adapter and rack of discrete count as a single connection. Each analog module counts as a single connection

Hardware Specifications

Specification	Description
Ports	1 RJ45 10/100 Mbps Ethernet port 1 Phoenix 3-pin power connector 1 Phoenix 3-pin connector network connector
Typical Power Consumption	200 mA @ 12 VDC or 100 mA @ 24 VDC
Maximum Power Dissipation	2.4 W
Operating Temp	32°F to 122°F (0 °C to 50 °C)
Storage Temperature	-40°F to 185°F (-40 °C to 85 °C)
Dimensions	107 x 126 x 34 mm (4.18 x 4.97 x 1.33 in) Not including connectors
Humidity	5% to 95% RH, with no condensation

Desktop use or DIN Rail Mountable



Where Automation
Connects™

Ordering Information

To order this product, please use the following:

EtherNet/IP™ to Remote I/O or DH+ Gateway

AN-X2-AB-DHRIO

This gateway replaces these part numbers:

AN-X-AB-SCAN

AN-X-AB-RIO-DRV

AN-X-AB-RIO-HMI

AN-X-AB-DHP

AN-X-AB-ADAPT

AN-X-AB-DHRIO

To place an order, please contact your local ProSoft Technology distributor. For a list of ProSoft Technology distributors near you, go to:

www.prosoft-technology.com
and select *Where to Buy* from the menu.

Copyright © 2022 ProSoft Technology, Inc.

All Rights Reserved. October 5, 2022

For Public Use.

Specifications subject to change without notice.