



## Liquid & Gas Flow Computer

### MVI69-AFC

The MVI Liquid & Gas Flow Computer Module is a CompactLogix backplane compatible module that allows CompactLogix processors to easily support flow applications with 8 meter runs performing measurement of hydrocarbon gases or liquids using AGA 3, 7, 8 and API 2540 measurement standards.

### Features and Benefits

The MVI69-AFC is an in-rack Liquid & Gas Flow Computer Module for the CompactLogix platform. The MVI69-AFC Flow computer module supports 8 meter channels for the measurement of hydrocarbon gases and liquids using currently accepted industry measurement standards.

The module calculates flow rates, accumulated volumes, accumulated mass and accumulated energy (heating value). The calculation results are transferred back to the Processor memory for use in the application ladder program or for transfer back to a SCADA host.

### General Specifications

- Single Slot – 1769 backplane compatible
- The module is recognized as an Input/Output module and has access to processor memory for data transfer between processor and module
- Ladder Logic is used for data transfer between module and processor.
- Configuration data obtained through user-defined ladder. Sample ladder file included
- Supports all CompactLogix processors: L20/L30/L31/L32/L35

### Hardware Specifications

Specification	Description
Dimensions	Standard 1769 Single-slot module
Current Load	800 mA max@ 5 VDC Power supply distance rating of 2
Operating Temp.	0 to 60°C (32 to 140°F)
Storage Temp.	40 to 85°C (40 to 185°F)
Relative Humidity	5 to 95% (non-condensing)
LED Indicators	Power and Module Status Application Status Serial Port Activity Serial Activity and Error Status

### Liquid & Gas Flow Computer MVI69-AFC

*The MVI69-AFC module is the ideal solution for the many applications where hydrocarbon flow and SCADA communication must be added to the CompactLogix platform.*

*Applications using the MVI69-AFC module can be found mainly in the oil and gas industrial sectors.*

### How to Contact Us: Sales and Support

All ProSoft Technology products are backed with unlimited technical support. Contact our worldwide Technical Support team directly by phone or email:

#### Asia Pacific

+603.7724.2080, asiapc@prosoft-technology.com  
Languages spoken include: Chinese, Japanese, English

#### Europe – Middle East – Africa

+33 (0) 5.34.36.87.20, support.EMEA@prosoft-technology.com  
Languages spoken include: French, English

#### North America

+1.661.716.5100, support@prosoft-technology.com  
Languages spoken include: English, Spanish

#### Latin America (Sales only)

+1.281.298.9109, latinam@prosoft-technology.com  
Languages spoken include: Spanish, English

#### Brasil

+55-11.5084.5178, eduardo@prosoft-technology.com  
Languages spoken include: Portuguese, English

Specification	Description
CFG Port (CFG)	RJ45 (DB-9F with supplied cable) RS-232 only No hardware handshaking
App Ports (P1,P2) (Serial modules)	RJ45 (DB-9F with supplied cable) RS-232 handshaking configurable 500V Optical isolation from backplane
Shipped with Unit	RJ45 to DB-9M cables for each port 6-foot RS-232 configuration Cable

## Functional Specifications

The AFC module operates as a powerful flow computer module, augmenting the operation of the CompactLogix processor by providing a dedicated and accurate set of flow calculations; the results of which are easily available to process monitoring and control applications developed in the CompactLogix.

The module is highly-configurable (see PSW-AFC), allowing each of the 8 meter runs to be individually set up to meet the specific requirements of an application. Some of the configurable parameters include:

## Configurable options

- Gas analysis concentrations for any of all 21 components
- Physical data for all meter runs including, orifice and pipe diameters, selection of type of taps and tap location etc.
- Reference pressure, temperature and local atmospheric conditions
- Default process and operating parameters like DP threshold for flow cutoff etc.
- Metric or imperial units
- User selectable units for totalizers and flow rates on a per channel basis
- Resettable and/or non-resettable totalizers for every meter channel
- Process I/O: analog inputs (pressure, temperature, diff pressure) from analog modules and pulse inputs from pulse/frequency input modules in CompactLogix I/O rack
- Number of meter channels: 8 differential (AGA3) or linear (AGA7) Gas; MPMS 12.2 Liquid
- Calculation methods: AGA3-1992, AGA 7, AGA8-1992 (detailed characterization method), API MPMS Ch12.2 API 2540
- Meter scan time under 1 second for all 8 channels
- Product measurement: hydrocarbon gases and liquids
- Data archiving: Hourly for 2 days for each meter run (48 records per channel), Daily for 35 days (optional extended archives up to 1260 hourly and 350 daily).

All archived data is available in the onboard Modbus memory map (archive size and contents are fully-configurable)

- Event log report for all security sensitive configuration data (for example, orifice diameter) are date and time stamped and mapped to the local Modbus memory map. This data can be imported into any spreadsheet program and saved to disk or printed as hard copy.

## Modbus interface

- The two Modbus slave ports allow the unit to be used as a SCADA interface and to broaden access to the AFC module's data table.
- Either port may be configured for RTU or ASCII Modbus mode.
- Modbus table may be re-mapped for user assigned contiguous register polling from a SCADA master (up to 20,000 registers).
- Port 3 can be configured as a Modbus Master port to poll data from a remote chromatograph device.

## Additional Products

ProSoft Technology offers a full complement of hardware and software solutions for a wide variety of industrial communication platforms.

Visit our web site at <http://www.prosoft-technology.com> for a complete list of products.

## Ordering Information

To order this product, please use the following:

**MVI69-AFC**          Liquid & Gas Flow Computer

To place an order, please contact your local ProSoft Technology distributor. For a list of ProSoft distributors near you, go to <http://www.prosoft-technology.com>

### Distributors:

Place your order by email or fax to:

### North American / Latin American / Asia Pacific

orders@prosoft-technology.com,  
fax to +1 661.716.5101

### Europe

europe@prosoft-technology.com,  
fax to +33 (0) 5.61.78.40.52

Copyright © ProSoft Technology, Inc. 2000 - 2007. All Rights Reserved.  
January 29, 2007