

# DATASHEET

## PROFIBUS DP Master/Slave to EtherNet/IP™ Gateway PLX51-PBM

The PLX51-PBM gateway provides connectivity to EtherNet/IP™ networks for PROFIBUS DP networks by operating as either a Master or Slave device on the PROFIBUS DP network.

For easy integration to a Rockwell Automation Controller, the gateway and configuration software create dynamic AOI's based on the user configuration to add logical tag names to the PLC project file. Thus, reducing the overall programming time.

With advanced tools such as PROFIBUS device discovery and a built-in PROFIBUS DP packet capture utility, PROFIBUS DP network commissioning time can be greatly reduced.

Dual Ethernet ports of the module can support either DLR (Device Level Ring) topology, or can be used as an embedded switch for flexible installation options.

With support for up to 1536 bytes of Input and Output data, and up to 4 EtherNet/IP connections back to the processor, this module provides performance and data throughput back to the processor for even the most demanding of PROFIBUS applications.

When used as a PROFIBUS DP slave, the module can operate as 1 to 10 slaves, providing up to 1536 bytes of Input and Output Cyclic I/O data between EtherNet/IP devices and a PROFIBUS DP master.



### Features

- ◆ Supports DLR for EtherNet/IP™ networks
- ◆ PROFIBUS master or slave (with multi-slave support)
- ◆ PROFIBUS packet capture tool built in

### Configuration

The PLX50 Configuration Utility software is used for configuration and troubleshooting of the module. The stand-alone configuration utility allows users to define the setup and configuration of the PROFIBUS DP network, connections with Rockwell Automation controllers and devices over EtherNet/IP, and build custom Add-On Instructions (AOIs) to be imported into Studio 5000 applications.

With the ability to import custom AOI's into the Studio 5000 environment and advanced PROFIBUS DP tools such as the packet capture utility, commissioning time of a network can be greatly reduced.

## EtherNet/IP™ Server

As an EtherNet/IP server, the gateway can support up to 4 Class 1 I/O connections back to a Controller on an EtherNet/IP network. Additionally, the server can respond to Class 3 messages from an EtherNet/IP client for the transfer of Status and PROFIBUS DP data.

## PROFIBUS DP Master V1

Cyclic or acyclic data can be transferred with Class 1 or Class 2 DPV1 services, allowing communication with slave devices supporting PROFIBUS DPV0 or V1 protocols. The gateway acts as an input/output link between the PROFIBUS network and the EtherNet/IP protocol. Data transfer by the EtherNet/IP protocol is asynchronous from data transfer on the PROFIBUS network.

- ◆ Easy-to-use drag and drop configuration interface via ProSoft PLX50 Configuration Utility
- ◆ GSD file import library
- ◆ Monitoring and Modification of process data and DPV1 acyclic data
- ◆ Multi-drop on a PROFIBUS DPV1 network with other compatible devices
- ◆ Automatic project documentation, and Bus Parameter calculation
- ◆ Supports online slave diagnostics, and extended diagnostic data (DPV1)
- ◆ Auto baud detection at all valid PROFIBUS DPV1 rates up to 12 Mbps
- ◆ Master Status LED Indicators for Operations, Network Communication, Master Token-Hold and Network Configuration.
- ◆ Up to 125 Slaves can be connected with a repeater
- ◆ Up to 1536 cyclic bytes input and 1536 bytes output data
- ◆ Supports Extended Diagnostic Data
- ◆ Alarm Handling (DPV1)
- ◆ Supports Sync and Freeze commands
- ◆ Supports PROFIdrive 3.1 compliant parameter read and write operations
- ◆ Supports Multicast and Broadcast telegrams (DPV1)



Where Automation  
Connects™

## Global Distribution

We think like you do

ProSoft Technology® products are distributed and supported worldwide through a network of over 500 distributors in over 50 countries. Our knowledgeable distributors are familiar with your application needs. For a complete list of distributors, go to our web site at:

[www.prosoft-technology.com](http://www.prosoft-technology.com)

## Global Support

We are there for you

All ProSoft Technology products are backed with free, unlimited technical support. Contact our worldwide Technical Support team directly by phone or email.

## Global Offices

We are where you are

ProSoft Technology has regional offices worldwide available to help you with all your industrial application needs. If you need help choosing a ProSoft Technology solution for your particular application check out our contact information under distributor sales on the web site at:

[www.prosoft-technology.com](http://www.prosoft-technology.com)

Whether your application is large or small, our technical professionals are there to help you choose the right communication solution.

## Specifications

### Functions

#### EtherNet/IP™

Connector	RJ45
Conductors	CAT5 STP/UTP
ARP Connections	Max 40
TCP Connections	Max 40
CIP Connections	Max 10
Communication Rate	10/100Mbps
Duplex Mode	Full / Half / Auto Negotiate
Auto MDIX	Yes

#### PROFIBUS DP

Protocol	PROFIBUS DP Master or Slave
Baud Rate	9600, 19.200, 45.5 kbps, 93.75 kbps, 187.5 kbps, 500 kbps, 1.5 Mbps, 3 Mbps, 6 Mbps, 12 Mbps
Support	DPV0 or DPV1
Cyclic I/O data	Input: 1536 bytes Output: 1536 bytes
Stop bits	1

### Physical

Enclosure Rating	IP20, NEMA/UL Open Type
Temperature	-20 to 70 °C
Earth Connection	Yes, terminal based
Dimensions (H x W x D)	5.86 x 1.33 x 4.56 in 149 x 34 x 116 mm
Power Requirements	Input: 10 to 36V DC
Power Consumption	85mA @ 24V => 2.04W
Power Connector	3-way terminal
Conductors	24 to 18 AWG

### Hardware Specifications

Specification	Description
Emissions	IEC 61000-6-4
ESD Immunity	EN 61000-4-2
Radiated RF Immunity	IEC 61000-4-3
EFT/B Immunity	IEC 61000-4-4
Surge Immunity	IEC 61000-4-5
Conducted RF Immunity	IEC 61000-4-6

## Agency Approvals & Certifications

Please visit our website: [www.prosoft-technology.com](http://www.prosoft-technology.com)



## Additional Products

ProSoft Technology® offers a full complement of hardware and software solutions for a wide variety of industrial communication platforms.

For a complete list of products, visit our web site at:  
[www.prosoft-technology.com](http://www.prosoft-technology.com)

## Ordering Information

To order this product, please use the following:

### PROFIBUS DP Master/Slave to EtherNet/IP™ Gateway

PLX51-PBM

To place an order, please contact your local ProSoft Technology distributor. For a list of ProSoft Technology distributors near you, go to:  
[www.prosoft-technology.com](http://www.prosoft-technology.com)  
and select *Where to Buy* from the menu.

Copyright © 2019 ProSoft Technology, Inc.  
All rights reserved. 8/29/2019  
v1.0

Specifications subject to change without notice.