

DATASHEET

EtherNet/IP, BACnet/IP, and BACnet MS/TP QuickServer Gateways PS-QS-1x10-0780

The QuickServer line of communication gateways are designed to link building automation driven networks with industrial control networks. The PS-QS-1x10-0780 simultaneously supports EtherNet/IP, BACnet/IP, and BACnet MS/TP, allowing for any combination of protocols to be used. The QuickServer gateways are available with limits of up to 250 or 500 points of application data.

Custom configuration services are also available for the QuickServer gateways. The user will be asked to fill out a worksheet, and answer some basic questions pertaining to the application, and a custom configuration will be provided along with the unit, reducing time to commission.



Specifications

Field Connections

- Ethernet 10/100 RJ45
- Two Serial RS-485 terminal (up to 115K baud)

Environment

- Operating temperature: -40°F to 167°F (-40°C to 75°C)
- Relative humidity: 5% to 90% RH, with no condensation

Power Requirements

- 9 to 30 Vdc or Vac or 5 Vdc
- Current draw 240mA @ 12V

Other

- Configuration/Diagnostic utilities
- Capacity: 250 or 500 Points
- Table, Wall or DIN rail mount

Physical Dimensions (W x D x H)

- 4.5 x 3.2 x 1.6 in. (11.5 x 8.3 x 4.1 cm)
- 0.4 lbs (0.2 Kg)

Approvals

Please visit our website: www.prosoft-technology.com

Ordering Information

To order this product, please use the following:

- PS-QS-1010-0780** 250 Points
- PS-QS-1510-0780** 500 Points

To place an order, please contact your local ProSoft Technology distributor. For a list of ProSoft Technology distributors near you, go to:

www.prosoft-technology.com and select *Where to Buy*.

LonWorks[®] is a trademark of Echelon Corporation
Metasys[®] is a trademark of Johnson Controls
BACnet[®] is a trademark of ASHRAE